

## REFERENCES

- Babalola, P. O., Bolu, C. A., Inegbenebor, A. O., & Odunfa, K. M. (2014). Development of Aluminium Matrix Composites : A review, 2, 1–11.
- El-kady, O., & Fathy, A. (2013). Effect of SiC particle size on the physical and mechanical properties of extruded Al matrix nanocomposites. *JOURNAL OF MATERIALS&DESIGN*. <http://doi.org/10.1016/j.matdes.2013.08.049>
- El-Kady, O., & Fathy, A. (2014). Effect of SiC particle size on the physical and mechanical properties of extruded Al matrix nanocomposites. *Materials & Design*, 54, 348–353. <http://doi.org/10.1016/j.matdes.2013.08.049>
- Izadi, H., Nolting, A., Munro, C., Bishop, D. P., Plucknett, K. P., & Gerlich, A. P. (2013). Friction stir processing of Al/SiC composites fabricated by powder metallurgy. *Journal of Materials Processing Tech.* <http://doi.org/10.1016/j.jmatprotec.2013.05.012>
- Knowles, A. J., Jiang, X., Galano, M., & Audebert, F. (2014a). Microstructure and mechanical properties of 6061 Al alloy based composites with SiC nanoparticles. *JOURNAL OF ALLOYS AND COMPOUNDS*, 1–5. <http://doi.org/10.1016/j.jallcom.2014.01.134>
- Knowles, A. J., Jiang, X., Galano, M., & Audebert, F. (2014b). Microstructure and mechanical properties of 6061 Al alloy based composites with SiC nanoparticles. *Journal of Alloys and Compounds*, 615, S401–S405. <http://doi.org/10.1016/j.jallcom.2014.01.134>
- Kumar, S., & Balasubramanian, V. (2008). Developing a mathematical model to evaluate wear rate of AA7075 / SiC p powder metallurgy composites, 264, 1026–1034. <http://doi.org/10.1016/j.wear.2007.08.006>
- Min, S. (2009). Effects of volume fraction of SiC particles on mechanical properties of SiC / Al composites. *Transactions of Nonferrous Metals Society of China*, 19(6), 1400–1404. [http://doi.org/10.1016/S1003-6326\(09\)60040-6](http://doi.org/10.1016/S1003-6326(09)60040-6)
- Purohit, R., Rana, R. S., & Verma, C. S. (2012). FABRICATION OF Al-SiC p

- COMPOSITES THROUGH POWDER Metallurgy Process and Testing Of Properties, 2(3), 420–437.
- Rohatgi, P. K. (1993). Metal-matrix Composites I. *Defence Science Journal*, 43(4), 323–349.
- Rosso, M. (2006). Ceramic and metal matrix composites: Routes and properties, 175, 364–375. <http://doi.org/10.1016/j.jmatprotec.2005.04.038>
- Wang, H., Zhang, R., Hu, X., Wang, C., & Huang, Y. (2007). Characterization of a powder metallurgy SiC / Cu – Al composite, 7, 43–48. <http://doi.org/10.1016/j.jmatprotec.2007.06.002>
- Xiong, B., Xu, Z., Yan, Q., Lu, B., & Cai, C. (2011). Effects of SiC volume fraction and aluminum particulate size on interfacial reactions in SiC nanoparticulate reinforced aluminum matrix composites. *Journal of Alloys and Compounds*, 509(4), 1187–1191. <http://doi.org/10.1016/j.jallcom.2010.09.171>